



## BA30J-S/EP

**\$3,069.61 USD**

SKU: fc65ffa0f30b


Categories: [Encapsulated Isolation Transformer](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



### PRODUCT SPECIFICATIONS

|                     |                              |
|---------------------|------------------------------|
| Weight              | 520 lbs                      |
| Phases              | <a href="#">3</a>            |
| kVA                 | <a href="#">30</a>           |
| Connection          | <a href="#">3Ph-DY-5T-SD</a> |
| Primary Voltage     | <a href="#">600</a>          |
| Primary Max Current | <a href="#">28.9A</a>        |
| Primary Markings    | <a href="#">H1-H2-3</a>      |
| Primary Terminals   | <a href="#">#2-14 AWG</a>    |



|                            |  |
|----------------------------|--|
| Secondary Voltage          | <a href="#">240Y/139</a>   |
| Secondary Max Current      | <a href="#">72.2A</a>  |
| Secondary Markings         | <a href="#">X0-X1-X2-X3</a>  |
| Secondary Terminals        | <a href="#">#2/0-6 AWG</a>   |
| Primary Taps               | <a href="#">+/- 2 x 2.5%</a>   |
| Conductor Material         | <a href="#">Aluminum</a>   |
| Temperatue Rise            | <a href="#">130°C</a>  |
| Insuation Class            | <a href="#">200°C</a>  |
| BIL (Insulation) Level     | <a href="#">10kV</a>   |
| Efficiency                 | <a href="#">N/A</a>  |
| Impedance                  | <a href="#">1.5 – 3.5%</a>   |
| Sound (db)                 | <a href="#">45</a>   |
| Enclosure Type             | <a href="#">NEMA 3R Indoor</a>   |
| Enclosure                  | <a href="#">E3R-3PEP-5</a>   |
| Finish                     | <a href="#">Polyster Powder Coat – ANSI/ASA 61 Grey</a>  |
| Standards & Certifications | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a> |