



BA75Q-M/Z3 \$6,955.00 CAD

SKU: 0a81fdfa184d Categories: Isolation Transformers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





PRODUCT SPECIFICATIONS

Weight	710 lbs
Phases	<u>3</u>
kVA	<u>75</u>
Connection	<u>3Ph-YY-5T-SD</u>
Primary Voltage	<u>600Y/347</u>

The quote is valid 30 days from 7 May 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.





Primary Max Current	<u>72.2A</u>
Primary Markings	<u>H0-H1-H2-H3</u>
Primary Terminals	<u>#2/0-6 AWG</u>
Secondary Voltage	<u>208Y/120</u>
Secondary Max Current	<u>208.2A</u>
Secondary Markings	<u>X0-X1-X2-X3</u>
Secondary Terminals	600MCM-2
Primary Taps	<u>+/- 2 x 2.5%</u>
Conductor Material	Aluminum
Insuation Class	<u>220°C</u>
BIL (Insulation) Level	<u>10kV</u>
Impedance	<u>4.0 - 6.0%</u>
Sound (db)	<u>50</u>
Enclosure Type	NEMA 3R Indoor
Enclosure	<u>E3R-7</u>
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	<u>CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015</u> <u>Registered</u>
Efficiency	<u>98.60%</u>