OFFICIAL QUOTE

BC112Q-M/Z3






BC112Q-M/Z3


\$9,286.15 USD

SKU: 0a2bb5290170

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





PRODUCT SPECIFICATIONS

| Weight | 950 lbs |
|-----------------|--------------|
| Phases | 3 |
| kVA | 112.5 |
| Connection | 3Ph-YY-5T-SD |
| Primary Voltage | 600Y/347 |



OFFICIAL QUOTE

BC112Q-M/Z3



| Primary Max Current | <u>108.3A</u> |
|----------------------------|--|
| Primary Markings | <u>H0-H1-H2-H3</u> |
| Primary Terminals | 300MCM-6 |
| Secondary Voltage | <u>208Y/120</u> |
| Secondary Max Current | <u>312.3A</u> |
| Secondary Markings | <u>X0-X1-X2-X3</u> |
| Secondary Terminals | <u>Pads</u> |
| Primary Taps | <u>+/- 2 x 2.5%</u> |
| Conductor Material | <u>Copper</u> |
| Insuation Class | 220°C |
| BIL (Insulation) Level | <u>10kV</u> |
| Impedance | 4.0 - 6.0% |
| Sound (db) | <u>50</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure | <u>E3R-8</u> |
| Finish | Polyster Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Efficiency | 98.74% |