



BC2J-M/EP

\$1,607.00 CAD

SKU: d2a804776a37

Categories: [Encapsulated Isolation Transformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



PRODUCT SPECIFICATIONS

| | |
|------------------------|---------------------|
| Weight | 150 lbs |
| Phases | <u>3</u> |
| kVA | <u>2</u> |
| Connection | <u>3Ph-DY-NT-SD</u> |
| Primary Voltage | <u>600</u> |



| | |
|---------------------------------------|--|
| Primary Max Current | 1.9A |
| Primary Markings | H1-H2-3 |
| Primary Terminals | #2-14 AWG |
| Secondary Voltage | 208Y/120 |
| Secondary Max Current | 5.6A |
| Secondary Markings | X0-X1-X2-X3 |
| Secondary Terminals | #2-14 AWG |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Temperatue Rise | 130°C |
| Insuation Class | 200°C |
| BIL (Insulation) Level | 10kV |
| Efficiency | N/A |
| Impedance | 1.5 – 3.5% |
| Sound (db) | 40 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure | E3R-3PEP-1 |
| Finish | Polyster Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |