



BC30J-M/EP \$5,196.53 USD

SKU: a7165765d701 Categories: Encapsulated Isolation Transformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





PRODUCT SPECIFICATIONS

| Weight | 520 lbs |
|---------------------|---------------------|
| Phases | 3 |
| kVA | <u>30</u> |
| Connection | <u>3Ph-DY-5T-SD</u> |
| Primary Voltage | <u>600</u> |
| Primary Max Current | <u>28.9A</u> |
| Primary Markings | <u>H1-H2-3</u> |
| Primary Terminals | <u>#2-14 AWG</u> |



BC30J-M/EP



| Secondary Voltage | <u>208Y/120</u> |
|----------------------------|---|
| Secondary Max Current | <u>83.3A</u> |
| Secondary Markings | <u>X0-X1-X2-X3</u> |
| Secondary Terminals | <u>#2/0-6 AWG</u> |
| Primary Taps | <u>+/- 2 x 2.5%</u> |
| Conductor Material | <u>Copper</u> |
| Temperatue Rise | <u>130°C</u> |
| Insuation Class | <u>200°C</u> |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency | <u>N/A</u> |
| Impedance | <u>1.5 – 3.5%</u> |
| Sound (db) | <u>45</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure | E3R-3PEP-5 |
| Finish | Polyster Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |