




# BC6Q-M

## \$1,977.00 CAD


SKU: f4987c486678  
Categories: [Isolation Transformers](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



### PRODUCT SPECIFICATIONS

|                     |                              |
|---------------------|------------------------------|
| Weight              | 120 lbs                      |
| Phases              | <a href="#">3</a>            |
| kVA                 | <a href="#">6</a>            |
| Connection          | <a href="#">3Ph-YY-3T-SD</a> |
| Primary Voltage     | <a href="#">600Y/347</a>     |
| Primary Max Current | <a href="#">5.8A</a>         |



|                            |                                                                                                      |
|----------------------------|------------------------------------------------------------------------------------------------------|
| Primary Markings           | <a href="#">H0-H1-H2-H3</a>                                                                          |
| Primary Terminals          | <a href="#">Terminal Blocks</a>                                                                      |
| Secondary Voltage          | <a href="#">208Y/120</a>                                                                             |
| Secondary Max Current      | <a href="#">16.7A</a>                                                                                |
| Secondary Markings         | <a href="#">X0-X1-X2-X3</a>                                                                          |
| Secondary Terminals        | <a href="#">Terminal Blocks</a>                                                                      |
| Primary Taps               | <a href="#">+/- 1 x 5%</a>                                                                           |
| Conductor Material         | <a href="#">Copper</a>                                                                               |
| Insuation Class            | <a href="#">220°C</a>                                                                                |
| BIL (Insulation) Level     | <a href="#">10kV</a>                                                                                 |
| Impedance                  | <a href="#">5.5 – 7.0%</a>                                                                           |
| Sound (db)                 | <a href="#">40</a>                                                                                   |
| Enclosure Type             | <a href="#">NEMA 3R Indoor</a>                                                                       |
| Enclosure                  | <a href="#">E3R-4</a>                                                                                |
| Finish                     | <a href="#">Polyster Powder Coat – ANSI/ASA 61 Grey</a>                                              |
| Standards & Certifications | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a> |
| Efficiency                 | <a href="#">N/A</a>                                                                                  |