



## CE200H-K

**\$1,887.00 CAD**

SKU: 7f5b9c36da6d

Categories: [Control Transformers](#)

### PRODUCT SPECIFICATIONS

|                     |                              |
|---------------------|------------------------------|
| Weight              | 12 lbs                       |
| Phases              | <a href="#">1</a>            |
| VA                  | <a href="#">200</a>          |
| Connection          | <a href="#">1Ph-CT-SD-SD</a> |
| Primary Voltage     | <a href="#">480</a>          |
| Primary Max Current | <a href="#">0.42A</a>        |



|                            |  |
|----------------------------|--|
| Primary Markings           | <a href="#">H1-H2</a>  |
| Primary Terminals          | <a href="#">Leads</a>  |
| Secondary Voltage          | <a href="#">120/240</a>  |
| Secondary Max Current      | <a href="#">1.67A</a>  |
| Secondary Markings         | <a href="#">X1-X2-X3-X4</a>  |
| Secondary Terminals        | <a href="#">Leads</a>  |
| Primary Taps               | <a href="#">N/A</a>  |
| Conductor Material         | <a href="#">Copper</a>   |
| Temperatue Rise            | <a href="#">80°C</a>   |
| Insuation Class            | <a href="#">130°C</a>  |
| BIL (Insulation) Level     | <a href="#">10kV</a>   |
| Efficiency                 | <a href="#">N/A</a>  |
| Impedance                  | <a href="#">5.0 – 7.0%</a>   |
| Sound (db)                 | <a href="#">40</a>   |
| Enclosure Type             | <a href="#">Type-1 Indoor</a>  |
| Enclosure                  | <a href="#">See Chart</a>  |
| Standards & Certifications | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered</a> |
| Finish                     | <a href="#">Semigloss – BlackSemigloss – Black</a>   |