





CE200H-L \$1,389.72 USD

SKU: 4fc0f0a49686 Categories: <u>Control Transformers</u>

PRODUCT SPECIFICATIONS

Weight	12 lbs
Phases	1
VA	200
Connection	<u>1Ph-CT-SD-SD</u>
Primary Voltage	<u>480</u>
Primary Max Current	<u>0.42A</u>

The quote is valid 30 days from 20 April 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.





Primary Markings	<u>H1-H2</u>
Primary Terminals	<u>Leads</u>
Secondary Voltage	240/480
Secondary Max Current	<u>0.83A</u>
Secondary Markings	<u>X1-X2-X3-X4</u>
Secondary Terminals	<u>Leads</u>
Primary Taps	<u>N/A</u>
Conductor Material	<u>Copper</u>
Temperatue Rise	<u>80°C</u>
Insuation Class	<u>130°C</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency	<u>N/A</u>
Impedance	<u>5.0 – 7.0%</u>
Sound (db)	<u>40</u>
Enclosure Type	<u>Type-1 Indoor</u>
Enclosure	See Chart
Standards & Certifications	<u>CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015</u> <u>Registered</u>
Finish	<u>Semigloss – BlackSemigloss – Black</u>