CE3000B-K

$1,059.00 CAD

SKU: 710cb35b2324
Categories: Control Transformers

PRODUCT SPECIFICATIONS

Weight	70 lbs
Phases	1
VA	3000
Connection	1Ph-CT-SD-SD
Primary Voltage	208
Primary Max Current	14.42A
Primary Markings	H1-H2
Primary Terminals	Leads
Secondary Voltage	120/240

The quote is valid 30 days from 18 April 2025. The price does not include: "Special Features", freight and possible taxes.
Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.

Secondary Max Current	25A
Secondary Markings	X1-X2-X3-X4
Secondary Terminals	Leads
Primary Taps	N/A
Conductor Material	Copper
Temperatue Rise	115°C
Insuation Class	180°C
BIL (Insulation) Level	10kV
Efficiency	N/A
Impedance	5.0 – 7.0%
Sound (db)	40
Enclosure Type	Type-1 Indoor
Enclosure	See Chart
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered
Finish	Semigloss – BlackSemigloss – Black