



**250VA 120/240 VOLTS TO 12/24
VOLTS SINGLE PHASE CONTROL
TRANSFORMER**



250VA 120/240 VOLTS TO 12/24 VOLTS SINGLE PHASE CONTROL TRANSFORMER

\$209.30 CAD



Single Phase Control Transformer with a capacity of 250VA, transforming 120/240 Volts to 12/24 Volts

SKU: CS250K-Z

Categories: [Control Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES

VA Rating	Overall Dimensions					Mounting Studs	Mounting Studs
	A	B	C	D	E		
25	3	3	2.5	2.5	3.13	0.25	0.625
50	3	3	2.5	2.5	3.13	0.25	0.625
100	3	4	2.5	2.5	3	0.375	0.25
150	3.75	4.25	3.13	3.25	3.5	0.45	0.25
200	3.75	4.5	3.13	3.25	3.5	0.45	0.25
250	3.75	5	3.13	3.25	3.5	0.45	0.31
350	4.5	5	3.75	3.75	3.75	0.475	0.31
500	5.25	5.5	4.38	4.5	3.75	0.475	0.31
750	5.25	5.5	4.38	4.5	3.75	0.475	0.31
1000	5.75	6.5	4.38	4.5	3.75	0.475	0.31
1500	6.75	7.25	4.69	5	3.75	0.525	0.31
2000	7.5	7.5	6.25	6	4.25	0.525	0.31
3000	7.5	8.75	6.25	6	5.5	0.6	0.31
5000	9	10	8	7	7	0.8	0.44



Single Phase Control Transformer with a capacity of 250VA, transforming 120/240 Volts to 12/24 Volts



PRODUCT SPECIFICATIONS

Weight	23 lbs
Phases	1
Connection	1Ph-CT-DD-SD
Primary Voltage	120/240
Primary Max Current	2.08A
Primary Markings	H1-H2-H3-H4
Primary Terminals	Terminals
Secondary Voltage	12/24
Secondary Max Current	20.83A
Secondary Markings	X1-X2-X3-X4
Secondary Terminals	Terminals
Primary Taps	N/A
Conductor Material	Copper
Temperature Rise	80°C
Insulation Class	130°C (Class B)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	5.0 – 7.0%
Sound (db)	40
Enclosure Type	Core & Coil
Enclosure Size	See Core & Coil Chart
Finish/Colour	N/A
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered



OFFICIAL QUOTE

250VA 120/240 VOLTS TO 12/24
VOLTS SINGLE PHASE CONTROL
TRANSFORMER



VA	250
Country/Manufacturer	Canada/RPM