



## 5000VA 347 VOLTS TO 120/240 VOLTS SINGLE PHASE CONTROL TRANSFORMER

**\$1,816.36 CAD**


Single Phase Control Transformer with a capacity  
of 5000VA, transforming 347 Volts to 120/240  
Volts

SKU: CS5000E-K

Categories: [Control Transformers](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES

| Volts  | Overall Dimensions | Mounting Dimensions |
|--------|--------------------|---------------------|
| Rating | A B C              | D E F               |
| 25     | 3 3 2.5            | 2.5 2.5 3.33        |
| 30     | 3 3 2.5            | 2.5 2.5 3.33        |
| 100    | 3 4 2.5            | 2.5 3 3.75          |
| 150    | 3.75 4.25 3.33     | 3.25 3.5 4.5        |
| 200    | 3.75 4.5 3.33      | 3.25 3.5 4.5        |
| 250    | 3.75 5 3.33        | 3.25 3.5 4.5        |
| 350    | 4.5 5 3.75         | 3.75 3.75 4.75      |
| 500    | 5.25 5 4.38        | 4.5 3.75 4.75       |
| 750    | 5.25 5.5 4.38      | 4.5 3.75 4.75       |
| 1000   | 5.25 6.5 4.38      | 4.5 3.75 4.75       |
| 1500   | 6.75 7.25 5.63     | 5 3.75 5.25         |
| 2000   | 7.5 7.5 6.25       | 6 4.25 5.25         |
| 3000   | 7.5 8.75 6.25      | 6 5.5 6.5           |
| 5000   | 9 10 8             | 7 8 8               |



Single Phase Control Transformer with a capacity of 5000VA, transforming 347 Volts to 120/240 Volts



## PRODUCT SPECIFICATIONS

|                            |  |
|----------------------------|--|
| Weight                     | 110 lbs  |
| Phases                     | <a href="#">1</a>  |
| Connection                 | <a href="#">1Ph-CT-SD-SD</a>   |
| Primary Voltage            | <a href="#">347</a>  |
| Primary Max Current        | <a href="#">14.41A</a>   |
| Primary Markings           | <a href="#">H1-H2</a>  |
| Primary Terminals          | <a href="#">Terminals</a>  |
| Secondary Voltage          | <a href="#">120/240</a>  |
| Secondary Max Current      | <a href="#">41.67A</a>   |
| Secondary Markings         | <a href="#">X1-X2-X3-X4</a>  |
| Secondary Terminals        | <a href="#">Terminals</a>  |
| Primary Taps               | <a href="#">N/A</a>  |
| Conductor Material         | <a href="#">Copper</a>   |
| Temperatue Rise            | <a href="#">115°C</a>  |
| Insuation Class            | <a href="#">180°C (Class F)</a>  |
| BIL (Insulation) Level     | <a href="#">10kV</a>   |
| Efficiency (@35% Load) %   | <a href="#">N/A</a>  |
| Impedance Range            | <a href="#">5.0 – 7.0%</a>   |
| Sound (db)                 | <a href="#">40</a>   |
| Enclosure Type             | <a href="#">Core &amp; Coil</a>  |
| Enclosure Size             | <a href="#">See Core &amp; Coil Chart</a>  |
| Finish/Colour              | <a href="#">N/A</a>  |
| Standards & Certifications | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered</a> |



OFFICIAL QUOTE

5000VA 347 VOLTS TO 120/240  
VOLTS SINGLE PHASE CONTROL  
TRANSFORMER



|                      |                            |
|----------------------|----------------------------|
| VA                   | <a href="#">5000</a>       |
| Country/Manufacturer | <a href="#">Canada/RPM</a> |