

OFFICIAL QUOTE

500VA 277 VOLTS TO 120/240 VOLTS SINGLE PHASE CONTROL TRANSFORMER





500VA 277 VOLTS TO 120/240 VOLTS SINGLE PHASE CONTROL TRANSFORMER

\$345.80 CAD


Single Phase Control Transformer with a capacity of 500VA, transforming 277 Volts to 120/240 Volts

SKU: CE500D-K

Categories: Control Transformers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES

Control 1	Transforme				s (inches)
VA	Overall Dimensions				
Rating	Α	В	С	Mounting Dimensions D x E	
25	3	6	3.5	1.375	4.375
50	3	6	3.5	1.375	4.375
100	3	6	3.5	1.375	4.375
150	3.5	6.658	3.13	3.25	5
200	3.5	6.658	3.13	3.25	5
250	3.5	6.658	3.13	3.25	5
350	4.125	6.5	3.75	3.75	7.875
500	4.875	7	4.38	4.5	5.5
750	4.875	7	4.38	4.5	5.5
1000	4.875	7	4.38	4.5	5.5
1500	5.625	9	5.63	5	7.25
2000	6.875	9.25	6.25	6	8
3000	6.875	9.25	6.25	6	8
5000	8	10.5	9.5	6	9



Single Phase Control Transformer with a capacity of 500VA, transforming 277 Volts to 120/240 Volts



OFFICIAL QUOTE



500VA 277 VOLTS TO 120/240 VOLTS SINGLE PHASE CONTROL TRANSFORMER

PRODUCT SPECIFICATIONS

Weight	14 lbs	
Phases	1	
Connection	1Ph-CT-SD-SD	
Primary Voltage	120/240	
Primary Max Current	1.81A	
Primary Markings	H1-H2	
Primary Terminals	<u>Leads</u>	
Secondary Voltage	120/240	
Secondary Max Current	4.17A	
Secondary Markings	X1-X2-X3-X4	
Secondary Terminals	<u>Leads</u>	
Primary Taps	N/A	
Conductor Material	Copper	
Temperatue Rise	<u>115°C</u>	
Insuation Class	180°C (Class F)	
BIL (Insulation) Level	<u>10kV</u>	
Efficiency (@35% Load) %	N/A	
Impedance Range	<u>5.0 - 7.0%</u>	
Sound (db)	40	
Enclosure Type	Type-1 Indoor	
Enclosure Size	See Enclosure Chart	
Finish/Colour	Semigloss - Black	
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered	



OFFICIAL QUOTE



500VA 277 VOLTS TO 120/240 VOLTS SINGLE PHASE CONTROL TRANSFORMER

VA	
Country/Manufacturer	Canada/RPM