



50VA 347 VOLTS TO 120/240 VOLTS SINGLE PHASE CONTROL TRANSFORMER

\$94.64 CAD


Single Phase Control Transformer with a capacity of 50VA, transforming 347 Volts to 120/240 Volts

SKU: CS50E-K

Categories: [Control Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES

Control Transformer Table of Dimensions (Inches)						
VA	Overall Dimensions			Mounting Centres		Mounting Slot
Rating	A	B	C	D	E	F
25	3	3	2.5	2.5	2.5	5.13
50	3	3	2.5	2.5	2.5	5.13
100	3	4	2.5	2.5	3	5.13
150	3.75	4.25	3.13	3.25	3.5	4.5
200	3.75	4.5	3.13	3.25	3.5	4.5
250	3.75	5	3.13	3.25	3.5	4.5
300	4.5	5	3.75	3.75	3.75	4.75
350	5.25	5	4.38	4.5	3.75	4.75
400	5.25	5.5	4.38	4.5	3.75	4.75
450	5.25	5.5	4.38	4.5	3.75	4.75
500	5.25	5.5	4.38	4.5	3.75	4.75
550	5.25	5.5	4.38	4.5	3.75	4.75
600	5.25	5.5	4.38	4.5	3.75	4.75
650	5.25	5.5	4.38	4.5	3.75	4.75
700	5.25	5.5	4.38	4.5	3.75	4.75
750	5.25	5.5	4.38	4.5	3.75	4.75
800	5.25	5.5	4.38	4.5	3.75	4.75
850	5.25	5.5	4.38	4.5	3.75	4.75
900	5.25	5.5	4.38	4.5	3.75	4.75
950	5.25	5.5	4.38	4.5	3.75	4.75
1000	5.25	5.5	4.38	4.5	3.75	4.75
1050	5.25	5.5	4.38	4.5	3.75	4.75
1100	5.25	5.5	4.38	4.5	3.75	4.75
1150	5.25	5.5	4.38	4.5	3.75	4.75
1200	5.25	5.5	4.38	4.5	3.75	4.75
1250	5.25	5.5	4.38	4.5	3.75	4.75
1300	5.25	5.5	4.38	4.5	3.75	4.75
1350	5.25	5.5	4.38	4.5	3.75	4.75
1400	5.25	5.5	4.38	4.5	3.75	4.75
1450	5.25	5.5	4.38	4.5	3.75	4.75
1500	5.25	5.5	4.38	4.5	3.75	4.75
1550	5.25	5.5	4.38	4.5	3.75	4.75
1600	5.25	5.5	4.38	4.5	3.75	4.75
1650	5.25	5.5	4.38	4.5	3.75	4.75
1700	5.25	5.5	4.38	4.5	3.75	4.75
1750	5.25	5.5	4.38	4.5	3.75	4.75
1800	5.25	5.5	4.38	4.5	3.75	4.75
1850	5.25	5.5	4.38	4.5	3.75	4.75
1900	5.25	5.5	4.38	4.5	3.75	4.75
1950	5.25	5.5	4.38	4.5	3.75	4.75
2000	5.25	5.5	4.38	4.5	3.75	4.75
2050	5.25	5.5	4.38	4.5	3.75	4.75
2100	5.25	5.5	4.38	4.5	3.75	4.75
2150	5.25	5.5	4.38	4.5	3.75	4.75
2200	5.25	5.5	4.38	4.5	3.75	4.75
2250	5.25	5.5	4.38	4.5	3.75	4.75
2300	5.25	5.5	4.38	4.5	3.75	4.75
2350	5.25	5.5	4.38	4.5	3.75	4.75
2400	5.25	5.5	4.38	4.5	3.75	4.75
2450	5.25	5.5	4.38	4.5	3.75	4.75
2500	5.25	5.5	4.38	4.5	3.75	4.75
2550	5.25	5.5	4.38	4.5	3.75	4.75
2600	5.25	5.5	4.38	4.5	3.75	4.75
2650	5.25	5.5	4.38	4.5	3.75	4.75
2700	5.25	5.5	4.38	4.5	3.75	4.75
2750	5.25	5.5	4.38	4.5	3.75	4.75
2800	5.25	5.5	4.38	4.5	3.75	4.75
2850	5.25	5.5	4.38	4.5	3.75	4.75
2900	5.25	5.5	4.38	4.5	3.75	4.75
2950	5.25	5.5	4.38	4.5	3.75	4.75
3000	5.25	5.5	4.38	4.5	3.75	4.75
3050	5.25	5.5	4.38	4.5	3.75	4.75
3100	5.25	5.5	4.38	4.5	3.75	4.75
3150	5.25	5.5	4.38	4.5	3.75	4.75
3200	5.25	5.5	4.38	4.5	3.75	4.75
3250	5.25	5.5	4.38	4.5	3.75	4.75
3300	5.25	5.5	4.38	4.5	3.75	4.75
3350	5.25	5.5	4.38	4.5	3.75	4.75
3400	5.25	5.5	4.38	4.5	3.75	4.75
3450	5.25	5.5	4.38	4.5	3.75	4.75
3500	5.25	5.5	4.38	4.5	3.75	4.75
3550	5.25	5.5	4.38	4.5	3.75	4.75
3600	5.25	5.5	4.38	4.5	3.75	4.75
3650	5.25	5.5	4.38	4.5	3.75	4.75
3700	5.25	5.5	4.38	4.5	3.75	4.75
3750	5.25	5.5	4.38	4.5	3.75	4.75
3800	5.25	5.5	4.38	4.5	3.75	4.75
3850	5.25	5.5	4.38	4.5	3.75	4.75
3900	5.25	5.5	4.38	4.5	3.75	4.75
3950	5.25	5.5	4.38	4.5	3.75	4.75
4000	5.25	5.5	4.38	4.5	3.75	4.75
4050	5.25	5.5	4.38	4.5	3.75	4.75
4100	5.25	5.5	4.38	4.5	3.75	4.75
4150	5.25	5.5	4.38	4.5	3.75	4.75
4200	5.25	5.5	4.38	4.5	3.75	4.75
4250	5.25	5.5	4.38	4.5	3.75	4.75
4300	5.25	5.5	4.38	4.5	3.75	4.75
4350	5.25	5.5	4.38	4.5	3.75	4.75
4400	5.25	5.5	4.38	4.5	3.75	4.75
4450	5.25	5.5	4.38	4.5	3.75	4.75
4500	5.25	5.5	4.38	4.5	3.75	4.75
4550	5.25	5.5	4.38	4.5	3.75	4.75
4600	5.25	5.5	4.38	4.5	3.75	4.75
4650	5.25	5.5	4.38	4.5	3.75	4.75
4700	5.25	5.5	4.38	4.5	3.75	4.75
4750	5.25	5.5	4.38	4.5	3.75	4.75
4800	5.25	5.5	4.38	4.5	3.75	4.75
4850	5.25	5.5	4.38	4.5	3.75	4.75
4900	5.25	5.5	4.38	4.5	3.75	4.75
4950	5.25	5.5	4.38	4.5	3.75	4.75
5000	5.25	5.5	4.38	4.5	3.75	4.75



Single Phase Control Transformer with a capacity of 50VA, transforming 347 Volts to 120/240 Volts



PRODUCT SPECIFICATIONS

Weight	3 lbs
Phases	1
Connection	1Ph-CT-SD-SD
Primary Voltage	347
Primary Max Current	0.14A
Primary Markings	H1-H2
Primary Terminals	Terminals
Secondary Voltage	120/240
Secondary Max Current	0.42A
Secondary Markings	X1-X2-X3-X4
Secondary Terminals	Terminals
Primary Taps	N/A
Conductor Material	Copper
Temperatue Rise	80°C
Insuation Class	130°C (Class B)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	5.0 – 7.0%
Sound (db)	40
Enclosure Type	Core & Coil
Enclosure Size	See Core & Coil Chart
Finish/Colour	N/A
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered



OFFICIAL QUOTE
50VA 347 VOLTS TO 120/240 VOLTS
SINGLE PHASE CONTROL
TRANSFORMER



VA	50
Country/Manufacturer	Canada/RPM