



## 50VA 347 VOLTS TO 120/240 VOLTS SINGLE PHASE CONTROL TRANSFORMER

**\$94.64 CAD**


Single Phase Control Transformer with a capacity of 50VA, transforming 347 Volts to 120/240 Volts

SKU: CS50E-K

Categories: [Control Transformers](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES

VA	Overall Dimensions				Mounting Centres		Mounting Slot	
Rating	A	B	C	D	E	F	G	H
25	3	3	2.5	2.5	2.5	5.13	0.25 x 0.625	
50	3	4	2.5	2.5	2.5	5.13	0.25 x 0.625	
100	3	4	2.5	2.5	3	5.75	0.25 x 0.625	
150	3.75	4.25	3.13	3.25	3.5	4.5	0.25 x 0.625	
200	3.75	4.5	3.13	3.25	3.5	4.5	0.25 x 0.625	
250	3.75	5	3.13	3.25	3.5	4.5	0.31 x 0.625	
300	4.5	5	3.75	3.75	3.75	4.75	0.31 x 0.625	
350	5.25	5	4.38	4.5	3.75	4.75	0.31 x 0.625	
400	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
450	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
500	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
550	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
600	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
650	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
700	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
750	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
800	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
850	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
900	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
950	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1000	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1050	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1100	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1150	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1200	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1250	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1300	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1350	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1400	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1450	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1500	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1550	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1600	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1650	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1700	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1750	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1800	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1850	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1900	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
1950	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2000	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2050	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2100	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2150	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2200	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2250	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2300	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2350	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2400	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2450	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2500	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2550	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2600	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2650	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2700	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2750	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2800	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2850	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2900	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
2950	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3000	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3050	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3100	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3150	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3200	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3250	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3300	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3350	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3400	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3450	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3500	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3550	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3600	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3650	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3700	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3750	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3800	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3850	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3900	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
3950	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4000	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4050	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4100	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4150	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4200	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4250	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4300	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4350	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4400	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4450	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4500	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4550	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4600	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4650	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4700	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4750	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4800	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4850	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4900	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
4950	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	
5000	5.25	5.5	4.38	4.5	3.75	4.75	0.31 x 0.625	



Single Phase Control Transformer with a capacity of 50VA, transforming 347 Volts to 120/240 Volts



## PRODUCT SPECIFICATIONS

Weight	3 lbs
Phases	<a href="#">1</a>
Connection	<a href="#">1Ph-CT-SD-SD</a>
Primary Voltage	<a href="#">347</a>
Primary Max Current	<a href="#">0.14A</a>
Primary Markings	<a href="#">H1-H2</a>
Primary Terminals	<a href="#">Terminals</a>
Secondary Voltage	<a href="#">120/240</a>
Secondary Max Current	<a href="#">0.42A</a>
Secondary Markings	<a href="#">X1-X2-X3-X4</a>
Secondary Terminals	<a href="#">Terminals</a>
Primary Taps	<a href="#">N/A</a>
Conductor Material	<a href="#">Copper</a>
Temperatue Rise	<a href="#">80°C</a>
Insuation Class	<a href="#">130°C (Class B)</a>
BIL (Insulation) Level	<a href="#">10kV</a>
Efficiency (@35% Load) %	<a href="#">N/A</a>
Impedance Range	<a href="#">5.0 – 7.0%</a>
Sound (db)	<a href="#">40</a>
Enclosure Type	<a href="#">Core &amp; Coil</a>
Enclosure Size	<a href="#">See Core &amp; Coil Chart</a>
Finish/Colour	<a href="#">N/A</a>
Standards & Certifications	<a href="#">CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered</a>



OFFICIAL QUOTE

50VA 347 VOLTS TO 120/240 VOLTS  
SINGLE PHASE CONTROL  
TRANSFORMER



VA	<a href="#">50</a>
Country/Manufacturer	<a href="#">Canada/RPM</a>