




CS1000K-L

**\$372.65 USD**

SKU: ee02b496d192

Categories: [Control Transformers](#)

## PRODUCT SPECIFICATIONS

|                       |                              |
|-----------------------|------------------------------|
| Weight                | 50 lbs                       |
| Phases                | <a href="#">1</a>            |
| VA                    | <a href="#">1000</a>         |
| Connection            | <a href="#">1Ph-CT-DD-SU</a> |
| Primary Voltage       | <a href="#">120/240</a>      |
| Primary Max Current   | <a href="#">8.33A</a>        |
| Primary Markings      | <a href="#">X1-X2-X3-X4</a>  |
| Primary Terminals     | <a href="#">Terminals</a>    |
| Secondary Voltage     | <a href="#">240/480</a>      |
| Secondary Max Current | <a href="#">4.17A</a>        |
| Secondary Markings    | <a href="#">H1-H2-H3-H4</a>  |
| Secondary Terminals   | <a href="#">Terminals</a>    |



|                            |                                                                                                      |
|----------------------------|------------------------------------------------------------------------------------------------------|
| Primary Taps               | <a href="#">N/A</a>                                                                                  |
| Conductor Material         | <a href="#">Copper</a>                                                                               |
| Temperatue Rise            | <a href="#">115°C</a>                                                                                |
| Insuation Class            | <a href="#">180°C</a>                                                                                |
| BIL (Insulation) Level     | <a href="#">10kV</a>                                                                                 |
| Efficiency                 | <a href="#">N/A</a>                                                                                  |
| Impedance                  | <a href="#">5.0 – 7.0%</a>                                                                           |
| Sound (db)                 | <a href="#">40</a>                                                                                   |
| Enclosure Type             | <a href="#">Core &amp; Coil</a>                                                                      |
| Enclosure                  | <a href="#">See Chart</a>                                                                            |
| Standards & Certifications | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered</a> |
| Finish                     | <a href="#">N/AN/A</a>                                                                               |