





CS150H-A \$140.00 CAD

SKU: c53e2471e390 Categories: Control Transformers

PRODUCT SPECIFICATIONS

Weight	18 lbs
Phases	1
VA	<u>150</u>
Connection	<u>1Ph-CT-SS-SU</u>
Primary Voltage	<u>480</u>
Primary Max Current	<u>0.31A</u>
Primary Markings	<u>H1-H2</u>
Primary Terminals	<u>Terminals</u>
Secondary Voltage	120
Secondary Max Current	<u>1.25A</u>
Secondary Markings	<u>X1-X2</u>

The quote is valid 30 days from 5 May 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.



CS150H-A



Secondary Terminals	Terminals
Primary Taps	N/A
Conductor Material	<u>Copper</u>
Temperatue Rise	<u>80°C</u>
Insuation Class	<u>130°C</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency	<u>N/A</u>
Impedance	<u>5.0 – 7.0%</u>
Sound (db)	<u>40</u>
Enclosure Type	Core & Coil
Enclosure	See Chart
Standards & Certifications	<u>CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015</u> Registered
Finish	N/AN/A