





CS200H-L 175.00 CAD 166.25 CAD

SKU: 26d2acfb01d9 Categories: <u>Control Transformers</u>

PRODUCT SPECIFICATIONS

| Weight | 23 lbs |
|-----------------------|---------------------|
| Phases | 1 |
| VA | 200 |
| Connection | <u>1Ph-CT-SD-SD</u> |
| Primary Voltage | <u>480</u> |
| Primary Max Current | <u>0.42A</u> |
| Primary Markings | <u>H1-H2</u> |
| Primary Terminals | Terminals |
| Secondary Voltage | 240/480 |
| Secondary Max Current | <u>0.83A</u> |



CS200H-L



| Secondary Markings | <u>X1-X2-X3-X4</u> |
|----------------------------|---|
| Secondary Terminals | <u>Terminals</u> |
| Primary Taps | Ν/Α |
| Conductor Material | <u>Copper</u> |
| Temperatue Rise | <u>80°C</u> |
| Insuation Class | <u>130°C</u> |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency | <u>N/A</u> |
| Impedance | <u>5.0 – 7.0%</u> |
| Sound (db) | <u>40</u> |
| Enclosure Type | Core & Coil |
| Enclosure | See Chart |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered |
| Finish | N/AN/A |