




112.5KVA 600 VOLTS TO 240 VOLTS THREE PHASE ENCAPSULATED AUTOTRANSFORMER



\$13,033.00 CAD

Three Phase Encapsulated Autotransformer with a capacity of 112.5kVA, transforming 600Y Volts to 240Y Volts

SKU: RC112J-C/EP

Categories: [Encapsulated Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Encapsulated Autotransformer with a capacity of 112.5kVA, transforming 600Y Volts to 240Y Volts



PRODUCT SPECIFICATIONS

Weight	1160 lbs
Phases	3
kVA	112.5
Connection	3PhA-NT-1
Primary Voltage	600
Primary Markings	H1-H2-H3
Primary Terminals	300MCM-6
Secondary Voltage	240
Secondary Markings	X1-X2-X3
Secondary Terminals	600MCM-2
Primary Taps	N/A
Conductor Material	Copper
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	50
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-3PEP-7
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	130°C
Insuation Class	200°C (Class N)