




15KVA 480 VOLTS TO 208 VOLTS THREE PHASE ENCAPSULATED AUTOTRANSFORMER



\$2,536.00 CAD

Three Phase Encapsulated Autotransformer with a capacity of 15kVA, transforming 480Y Volts to 208Y Volts

SKU: RC15H-B/EP

Categories: [Encapsulated Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Encapsulated Autotransformer with a capacity of 15kVA, transforming 480Y Volts to 208Y Volts



PRODUCT SPECIFICATIONS

Weight	400 lbs
Phases	3
kVA	15
Connection	3PhA-NT-1
Primary Voltage	480
Primary Markings	H1-H2-H3
Primary Terminals	#2-14 AWG
Secondary Voltage	208
Secondary Markings	X1-X2-X3
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-3PEP-3
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	130°C
Insuation Class	200°C (Class N)