


OFFICIAL QUOTE

2KVA 480 VOLTS TO 240Y/139 VOLTS THREE PHASE ENCAPSULATED ISOLATION TRANSFORMER





2KVA 480 VOLTS TO 240Y/139 VOLTS THREE PHASE ENCAPSULATED ISOLATION TRANSFORMER


\$1,979.00 CAD


Three Phase Encapsulated Isolation Transformer with a capacity of 2kVA, transforming 480 Volts to 240Y/139 Volts

SKU: BC2H-S/EP

Categories: Encapsulated Isolation Transformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Encapsulated Isolation Transformer with a capacity of 2kVA, transforming 480 Volts to 240Y/139 Volts



OFFICIAL QUOTE



2KVA 480 VOLTS TO 240Y/139 VOLTS THREE PHASE ENCAPSULATED ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 150 lbs |
| Phases | 3 |
| kVA | 2 |
| Connection | 3Ph-DY-NT-SD |
| Primary Voltage | 480 |
| Primary Max Current | 2.4A |
| Primary Markings | H1-H2-3 |
| Primary Terminals | #2-14 AWG |
| Secondary Voltage | 240Y/139 |
| Secondary Max Current | <u>4.8A</u> |
| Secondary Markings | <u>X0-X1-X2-X3</u> |
| Secondary Terminals | #2-14 AWG |
| Primary Taps | N/A |
| Conductor Material | Copper |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | <u>1.5 – 3.5%</u> |
| Sound (db) | 40 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-3PEP-1</u> |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Country/Manufacturer | Canada/RPM |