


OFFICIAL QUOTE

75KVA 480 VOLTS TO 380Y/220 VOLTS THREE PHASE ENCAPSULATED ISOLATION TRANSFORMER






75KVA 480 VOLTS TO 380Y/220 VOLTS THREE PHASE ENCAPSULATED ISOLATION TRANSFORMER


\$12,608.00 CAD

Three Phase Encapsulated Isolation Transformer with a capacity of 75kVA, transforming 480 Volts to 380Y/220 Volts

SKU: BA75H-R/EP Categories: <u>Encapsulated Isolation Transformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Encapsulated Isolation Transformer with a capacity of 75kVA, transforming 480 Volts to 380Y/220 Volts



OFFICIAL QUOTE

75KVA 480 VOLTS TO 380Y/220 **VOLTS THREE PHASE ENCAPSULATED ISOLATION TRANSFORMER**



PRODUCT SPECIFICATIONS

| Weight | 1300 lbs |
|----------------------------|---|
| Phases | 3 |
| kVA | 75 |
| Connection | <u>3Ph-DY-5T-SD</u> |
| Primary Voltage | 480 |
| Primary Max Current | <u>90.2A</u> |
| Primary Markings | <u>H1-H2-3</u> |
| Primary Terminals | <u>#2/0-6 AWG</u> |
| Secondary Voltage | <u>380Y/220</u> |
| Secondary Max Current | <u>114A</u> |
| Secondary Markings | <u>X0-X1-X2-X3</u> |
| Secondary Terminals | <u>300MCM-6</u> |
| Primary Taps | <u>+/-2 x 2.5%</u> |
| Conductor Material | Aluminum |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | <u>1.5 - 3.5%</u> |
| Sound (db) | <u>50</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | E3R-3PEP-7 |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Country/Manufacturer | Canada/RPM |

The quote is valid 30 days from 30 May 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.