

OFFICIAL QUOTE

100KVA 380 VOLTS TO 110/220 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





100KVA 380 VOLTS TO 110/220 VOLTS SINGLE PHASE ISOLATION TRANSFORMER


\$11,303.84 CAD


Single Phase Isolation Transformer with a capacity of 100kVA, transforming 380 Volts to 110/220 Volts

SKU: SC100F-K2/Z3

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Isolation Transformer with a capacity of 100kVA, transforming 380 Volts to 110/220 Volts



OFFICIAL QUOTE



100KVA 380 VOLTS TO 110/220 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS			
Weight	711 lbs		
Phases	1		
kVA	100		
Connection	1Ph-2coil-5t-SD		
Primary Voltage	380		
Primary Max Current	<u>263.16A</u>		
Primary Markings	H1-H2		
Primary Terminals	600 MCM - 2		
Secondary Voltage	110/220		
Secondary Max Current	909.09A		
Secondary Markings	<u>X1-X2</u>		
Secondary Terminals	600 MCM - 2		
Primary Taps	+/- 2 x 2.5%		
Conductor Material	<u>Copper</u>		
BIL (Insulation) Level	<u>10kV</u>		
Efficiency (@35% Load) %	98.60% (DOE 2016/NRCan 2019)		
Impedance Range	4.0 - 6.0%		
Sound (db)	<u>50</u>		
Enclosure Type	NEMA 3R Indoor		
Enclosure Size	<u>E3R-8S</u>		
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey		
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered		
Temperatue Rise	150°C		



OFFICIAL QUOTE



100KVA 380 VOLTS TO 110/220 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

-	Insuation Class	<u>150°C</u>	_
	Country/Manufacturer	Canada/RPM	
	Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey	