



112.5KVA 416 VOLTS TO 416Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$12,434.69 CAD

Three Phase Isolation Transformer with a capacity of 112.5kVA, transforming 416 Volts to 416Y/240 Volts

SKU: BA112G-N/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 112.5kVA, transforming 416 Volts to 416Y/240 Volts



PRODUCT SPECIFICATIONS

| | |
|----------------------------|--|
| Weight | 890 lbs |
| Phases | 3 |
| kVA | 112.5 |
| Connection | 3Ph-DY-5T-SU |
| Primary Voltage | 416 |
| Primary Max Current | 156.13A |
| Primary Markings | H1-H2-H3 |
| Primary Terminals | 300 MCM – 6 |
| Secondary Voltage | 416Y/240 |
| Secondary Max Current | 156.13A |
| Secondary Markings | X0-X1-X2-X3 |
| Secondary Terminals | 300 MCM – 6 |
| Primary Taps | +/- 2 x 2.5% |
| Conductor Material | Aluminum |
| BIL (Insulation) Level | 10kV |
| Efficiency (@35% Load) % | 98.74% (DOE 2016/NRCan 2019) |
| Impedance Range | 4.0 – 6.0% |
| Sound (db) | 50 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | E3R-8 |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Temperatue Rise | 150°C |



112.5KVA 416 VOLTS TO 416Y/240
VOLTS THREE PHASE ISOLATION
TRANSFORMER

| | |
|----------------------|--|
| Insuation Class | 150°C |
| Country/Manufacturer | Canada/RPM |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |