

#### **OFFICIAL QUOTE**

### 112.5VA 460 VOLTS TO 380Y/220 VOLTS THREE PHASE ISOLATION TRANSFORMER





### 112.5VA 460 VOLTS TO 380Y/220 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$12,539.18 CAD

Three Phase Isolation Transformer with a capacity of 112.5kVA, transforming 460 Volts to 380Y/220 Volts

**SKU:** BA112H1-R/Z3

**Categories:** <u>Isolation Transformers</u>

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Isolation Transformer with a capacity of 112.5kVA, transforming 460 Volts to 380Y/220 Volts



#### **OFFICIAL QUOTE**



# 112.5VA 460 VOLTS TO 380Y/220 VOLTS THREE PHASE ISOLATION TRANSFORMER

### **PRODUCT SPECIFICATIONS**

Weight	890 lbs
Phases	3
kVA	112.5
Connection	3Ph-DY-5T-SD
Primary Voltage	460
Primary Max Current	141.2A
Primary Markings	H1-H2-H3
Primary Terminals	<u>300 MCM – 6</u>
Secondary Voltage	380Y/220
Secondary Max Current	170.93A
Secondary Markings	<u>X0-X1-X2-X3</u>
Secondary Terminals	300 MCM - 6
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	98.74% (DOE 2016/NRCan 2019)
Impedance Range	4.0 - 6.0%
Sound (db)	<u>50</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-8
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



#### **OFFICIAL QUOTE**



# 112.5VA 460 VOLTS TO 380Y/220 VOLTS THREE PHASE ISOLATION TRANSFORMER

Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey