



## 150KVA 208 VOLTS TO 110/220 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

**\$14,968.80 CAD**

Single Phase Isolation Transformer with a capacity of 150kVA, transforming 208 Volts to 110/220 Volts

**SKU:** SC150B-K2/Z3

**Categories:** [Isolation Transformers](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Isolation Transformer with a capacity of 150kVA, transforming 208 Volts to 110/220 Volts



## PRODUCT SPECIFICATIONS

Weight	851 lbs
Phases	<a href="#">1</a>
kVA	<a href="#">150</a>
Connection	<a href="#">1Ph-2coil-5t-SD</a>
Primary Voltage	<a href="#">208</a>
Primary Max Current	<a href="#">721.15A</a>
Primary Markings	<a href="#">H1-H2</a>
Primary Terminals	<a href="#">Pads</a>
Secondary Voltage	<a href="#">110/220</a>
Secondary Max Current	<a href="#">1363.64A</a>
Secondary Markings	<a href="#">X1-X2</a>
Secondary Terminals	<a href="#">Pads</a>
Primary Taps	<a href="#">+/- 2 x 2.5%</a>
Conductor Material	<a href="#">Copper</a>
BIL (Insulation) Level	<a href="#">10kV</a>
Efficiency (@35% Load) %	<a href="#">98.70% (DOE 2016/NRCan 2019)</a>
Impedance Range	<a href="#">4.0 – 6.0%</a>
Sound (db)	<a href="#">50</a>
Enclosure Type	<a href="#">NEMA 3R Indoor</a>
Enclosure Size	<a href="#">E3R-8S</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>
Standards & Certifications	<a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a>
Temperatue Rise	<a href="#">150°C</a>



150KVA 208 VOLTS TO 110/220  
VOLTS SINGLE PHASE ISOLATION  
TRANSFORMER

Insuation Class	<a href="#">150°C</a>
Country/Manufacturer	<a href="#">Canada/RPM</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>