



OFFICIAL QUOTE

150KVA 440 VOLTS TO 240Y/139
VOLTS THREE PHASE ISOLATION
TRANSFORMER



150KVA 440 VOLTS TO 240Y/139 VOLTS THREE PHASE ISOLATION TRANSFORMER



\$15,407.70 CAD

Three Phase Isolation Transformer with a capacity
of 150kVA, transforming 440 Volts to 240Y/139
Volts

SKU: BA150H2-S/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 150kVA, transforming 440 Volts to 240Y/139 Volts



OFFICIAL QUOTE

150KVA 440 VOLTS TO 240Y/139
VOLTS THREE PHASE ISOLATION
TRANSFORMER



PRODUCT SPECIFICATIONS

Weight	1100 lbs
Phases	3
kVA	150
Connection	3Ph-DY-5T-SD
Primary Voltage	440
Primary Max Current	196.82A
Primary Markings	H1-H2-H3
Primary Terminals	600 MCM – 2
Secondary Voltage	240Y/139
Secondary Max Current	360.84A
Secondary Markings	X0-X1-X2-X3
Secondary Terminals	600 MCM – 2
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	98.83% (DOE 2016/NRCan 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	50
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-8
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



OFFICIAL QUOTE

150KVA 440 VOLTS TO 240Y/139
VOLTS THREE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey