



## 15KVA 380 VOLTS TO 230Y/133 VOLTS THREE PHASE ISOLATION TRANSFORMER

**\$3,906.00 CAD**

Three Phase Isolation Transformer with a capacity of 15kVA, transforming 380 Volts to 230Y/133 Volts

**SKU:** BA15F-S1/Z3

**Categories:** [Isolation Transformers](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 15kVA, transforming 380 Volts to 230Y/133 Volts



PRODUCT SPECIFICATIONS

Weight	230 lbs
Phases	<a href="#">3</a>
kVA	<a href="#">15</a>
Connection	<a href="#">3Ph-DY-5T-SD</a>
Primary Voltage	<a href="#">380</a>
Primary Max Current	<a href="#">22.79A</a>
Primary Markings	<a href="#">H1-H2-H3</a>
Primary Terminals	<a href="#">#2-14 AWG</a>
Secondary Voltage	<a href="#">230Y/133</a>
Secondary Max Current	<a href="#">37.65A</a>
Secondary Markings	<a href="#">X0-X1-X2-X3</a>
Secondary Terminals	<a href="#">#2-14 AWG</a>
Primary Taps	<a href="#">+/- 2 x 2.5%</a>
Conductor Material	<a href="#">Aluminum</a>
BIL (Insulation) Level	<a href="#">10kV</a>
Efficiency (@35% Load) %	<a href="#">97.70% (DOE 2016/NRCan 2019)</a>
Impedance Range	<a href="#">4.0 – 6.0%</a>
Sound (db)	<a href="#">45</a>
Enclosure Type	<a href="#">NEMA 3R Indoor</a>
Enclosure Size	<a href="#">E3R-5</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>
Standards & Certifications	<a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a>
Temperatue Rise	<a href="#">150°C</a>



OFFICIAL QUOTE

15KVA 380 VOLTS TO 230Y/133  
VOLTS THREE PHASE ISOLATION  
TRANSFORMER



Insuation Class	<a href="#">150°C</a>
Country/Manufacturer	<a href="#">Canada/RPM</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>