

OFFICIAL QUOTE

15KVA 380 VOLTS TO 347 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





15KVA 380 VOLTS TO 347 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$2,732.45 CAD

Single Phase Isolation Transformer with a capacity of 15kVA, transforming 380 Volts to 347 Volts

SKU: SC15F-E/Z3 Categories: Isolation Transformers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Isolation Transformer with a capacity of 15kVA, transforming 380 Volts to 347 Volts



OFFICIAL QUOTE

15KVA 380 VOLTS TO 347 VOLTS SINGLE PHASE ISOLATION TRANSFORMER



PRODUCT SPECIFICATIONS

Weight	215 lbs
Phases	1
kVA	15
Connection	1Ph-2coil-5t-SD
Primary Voltage	380
Primary Max Current	<u>39.47A</u>
Primary Markings	H1-H2
Primary Terminals	<u>#2-14 AWG</u>
Secondary Voltage	347
Secondary Max Current	43.23A
Secondary Markings	<u>X1-X2</u>
Secondary Terminals	<u>#2-14 AWG</u>
Primary Taps	<u>+/-2 x 2.5%</u>
Conductor Material	Copper
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	97.70% (DOE 2016/NRCan 2019)
Impedance Range	<u>4.0 - 6.0%</u>
Sound (db)	<u>45</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-4</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	<u>150°C</u>

The quote is valid 30 days from 18 June 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.



OFFICIAL QUOTE

15KVA 380 VOLTS TO 347 VOLTS SINGLE PHASE ISOLATION TRANSFORMER



_	Insuation Class	<u>150°C</u>
	Country/Manufacturer	Canada/RPM
	Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey