

15KVA 440 VOLTS TO 110/220 VOLTS
SINGLE PHASE ISOLATION
TRANSFORMER



15KVA 440 VOLTS TO
110/220 VOLTS SINGLE
PHASE ISOLATION
TRANSFORMER



\$2,810.15 CAD

Single Phase Isolation Transformer with a capacity of 15kVA, transforming 440 Volts to 110/220 Volts

SKU: SA15H2-K2/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Isolation Transformer with a capacity of 15kVA, transforming 440 Volts to 110/220 Volts



PRODUCT SPECIFICATIONS

Weight	143 lbs
Phases	1
kVA	15
Connection	1Ph-2coil-5t-SD
Primary Voltage	440
Primary Max Current	34.09A
Primary Markings	H1-H2
Primary Terminals	#2-14 AWG
Secondary Voltage	110/220
Secondary Max Current	136.36A
Secondary Markings	X1-X2
Secondary Terminals	#2-14 AWG
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	97.70% (DOE 2016/NRCAN 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-4
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperature Rise	150°C



OFFICIAL QUOTE

15KVA 440 VOLTS TO 110/220 VOLTS
SINGLE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey