



15VA 200 VOLTS TO 220/440 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$2,922.56 CAD

Single Phase Isolation Transformer with a capacity of 15kVA, transforming 200 Volts to 220/440 Volts

SKU: SA15B1-L2/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Isolation Transformer with a capacity of 15kVA, transforming 200 Volts to 220/440 Volts

15VA 200 VOLTS TO 220/440 VOLTS
SINGLE PHASE ISOLATION
TRANSFORMER



PRODUCT SPECIFICATIONS

Weight	143 lbs
Phases	1
kVA	15
Connection	1Ph-2coil-5T-SU
Primary Voltage	200
Primary Max Current	75.0A
Primary Markings	X1-X2
Primary Terminals	#2/0-6 AWG
Secondary Voltage	220/440
Secondary Max Current	68.18A
Secondary Markings	H1-H2
Secondary Terminals	#2/0-6 AWG
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	97.70% (DOE 2016/NRCan 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-4
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



OFFICIAL QUOTE

15VA 200 VOLTS TO 220/440 VOLTS
SINGLE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey