

OFFICIAL QUOTE

15VA 230 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER





15VA 230 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$4,062.24 CAD

Three Phase Isolation Transformer with a capacity of 15kVA, transforming 230 Volts to 220Y/127 Volts

SKU: BA15C1-S2/Z3

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Isolation Transformer with a capacity of 15kVA, transforming 230 Volts to 220Y/127 Volts



OFFICIAL QUOTE



15VA 230 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | | |
|----------------------------|--|--|
| Weight | 230 lbs | |
| Phases | 3 | |
| kVA | <u>15</u> | |
| Connection | 3Ph-DY-5T-SD | |
| Primary Voltage | 230 | |
| Primary Max Current | 37.65A | |
| Primary Markings | H1-H2-H3 | |
| Primary Terminals | #2-14 AWG | |
| Secondary Voltage | 220Y/127 | |
| Secondary Max Current | 39.36A | |
| Secondary Markings | <u>X0-X1-X2-X3</u> | |
| Secondary Terminals | #2-14 AWG | |
| Primary Taps | +/- 2 x 2.5% | |
| Conductor Material | Aluminum | |
| BIL (Insulation) Level | 10kV | |
| Efficiency (@35% Load) % | 97.70% (DOE 2016/NRCan 2019) | |
| Impedance Range | 4.0 - 6.0% | |
| Sound (db) | 45 | |
| Enclosure Type | NEMA 3R Indoor | |
| Enclosure Size | <u>E3R-5</u> | |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey | |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered | |
| Temperatue Rise | 150°C | |



OFFICIAL QUOTE



15VA 230 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER

| - | Insuation Class | 150°C |
|---|----------------------|--|
| | Country/Manufacturer | Canada/RPM |
| | Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |