



15VA 415 VOLTS TO 440Y/254 VOLTS THREE PHASE ISOLATION TRANSFORMER


\$3,812.26 CAD

Three Phase Isolation Transformer with a capacity of 15kVA, transforming 415 Volts to 440Y/254 Volts

SKU: BA15G2-P2/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 15kVA, transforming 415 Volts to 440Y/254 Volts



PRODUCT SPECIFICATIONS

Weight	230 lbs
Phases	3
kVA	15
Connection	3Ph-DY-5T-SU
Primary Voltage	415
Primary Max Current	20.87A
Primary Markings	X1-X2-X3
Primary Terminals	#2-14 AWG
Secondary Voltage	440Y/254
Secondary Max Current	19.68A
Secondary Markings	H0-H1-H2-H3
Secondary Terminals	#2-14 AWG
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	97.70% (DOE 2016/NRCAN 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-5
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperature Rise	150°C



OFFICIAL QUOTE

15VA 415 VOLTS TO 440Y/254 VOLTS
THREE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey