


#### **OFFICIAL QUOTE**

## 15VA 600 VOLTS TO 380 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





# 15VA 600 VOLTS TO 380 VOLTS SINGLE PHASE ISOLATION TRANSFORMER


\$2,513.85 CAD


Single Phase Isolation Transformer with a capacity of 15kVA, transforming 600 Volts to 380 Volts

**SKU:** SC15J-F/Z3

**Categories:** <u>Isolation Transformers</u>

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Isolation Transformer with a capacity of 15kVA, transforming 600 Volts to 380 Volts



## **OFFICIAL QUOTE**



# 15VA 600 VOLTS TO 380 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

## **PRODUCT SPECIFICATIONS**

| Weight                     | 215 lbs  |
|----------------------------|--|
| Phases                     | 1  |
| kVA                        | <u>15</u>  |
| Connection                 | 1Ph-2coil-5t-SD  |
| Primary Voltage            | 600  |
| Primary Max Current        | 25.0A  |
| Primary Markings           | H1-H2  |
| Primary Terminals          | #2-14 AWG  |
| Secondary Voltage          | 380  |
| Secondary Max Current      | 39.47A   |
| Secondary Markings         | <u>X1-X2</u>   |
| Secondary Terminals        | #2-14 AWG  |
| Primary Taps               | +/- 2 x 2.5%   |
| Conductor Material         | Copper   |
| BIL (Insulation) Level     | 10kV   |
| Efficiency (@35% Load) %   | 97.70% (DOE 2016/NRCan 2019)   |
| Impedance Range            | 4.0 - 6.0%   |
| Sound (db)                 | 45   |
| Enclosure Type             | NEMA 3R Indoor   |
| Enclosure Size             | E3R-4  |
| Finish/Colour              | Polyester Powder Coat - ANSI/ASA 61 Grey   |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Temperatue Rise            | 150°C  |



## **OFFICIAL QUOTE**



# 15VA 600 VOLTS TO 380 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

| Insuation Class      | 150°C                                    | - |
|----------------------|--|---|
| Country/Manufacturer | Canada/RPM                               |   |
| Finish/Colour        | Polyester Powder Coat – ANSI/ASA 61 Grey |   |