


OFFICIAL QUOTE

1VA 460 VOLTS TO 230/460 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





1VA 460 VOLTS TO 230/460 VOLTS SINGLE PHASE ISOLATION TRANSFORMER


\$854.77 CAD


Single Phase Isolation Transformer with a capacity of 1kVA, transforming 460 Volts to 230/460 Volts

SKU: SC1H1-L1

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Isolation Transformer with a capacity of 1kVA, transforming 460 Volts to 230/460 Volts



OFFICIAL QUOTE



1VA 460 VOLTS TO 230/460 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 35 lbs |
| Phases | 1 |
| kVA | 1 |
| Connection | 1Ph-1coil-3T-SD |
| Primary Voltage | 460 |
| Primary Max Current | 2.17A |
| Primary Markings | H1-H2 |
| Primary Terminals | #2-14 AWG |
| Secondary Voltage | 230/460 |
| Secondary Max Current | 4.35A |
| Secondary Markings | <u>X1-X2</u> |
| Secondary Terminals | #2-14 AWG |
| Primary Taps | +/- 1 x 5% |
| Conductor Material | Copper |
| BIL (Insulation) Level | 10kV |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | <u>5.0 - 7.0%</u> |
| Sound (db) | 40 |
| Enclosure Type | NEMA 1 |
| Enclosure Size | <u>E1-0</u> |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Temperatue Rise | 115°C |



OFFICIAL QUOTE



1VA 460 VOLTS TO 230/460 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

| Insuation Class | 115°C |
|----------------------|--|
| Country/Manufacturer | Canada/RPM |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |