



200KVA 120 VOLTS TO 110/220 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$13,790.70 CAD

Single Phase Isolation Transformer with a capacity
of 200kVA, transforming 120 Volts to 110/220
Volts

SKU: SA200A-K2/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Isolation Transformer with a capacity of 200kVA, transforming 120 Volts to 110/220 Volts



PRODUCT SPECIFICATIONS

Weight	1015 lbs
Phases	1
kVA	200
Connection	1Ph-2coil-5t-SD
Primary Voltage	120
Primary Max Current	1666.67A
Primary Markings	H1-H2
Primary Terminals	Pads
Secondary Voltage	110/220
Secondary Max Current	1818.18A
Secondary Markings	X1-X2
Secondary Terminals	Pads
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	98.74% (DOE 2016/NRCan 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	55
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-9S
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



OFFICIAL QUOTE

200KVA 120 VOLTS TO 110/220
VOLTS SINGLE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey