

#### **OFFICIAL QUOTE**

## 200KVA 380 VOLTS TO 415 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





# 200KVA 380 VOLTS TO 415 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$21,180.25 CAD


Single Phase Isolation Transformer with a capacity of 200kVA, transforming 380 Volts to 415 Volts

**SKU:** SC200F-G2/Z3

**Categories:** <u>Isolation Transformers</u>

### **SCHEMATIC/DIAGRAM AND DIMENSION PICTURES**





Single Phase Isolation Transformer with a capacity of 200kVA, transforming 380 Volts to 415 Volts



#### **OFFICIAL QUOTE**



## 200KVA 380 VOLTS TO 415 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

#### **PRODUCT SPECIFICATIONS**

PRODUCT SPECIFICATIONS		
Weight	1170 lbs	
Phases	1	
kVA	200	
Connection	1Ph-2coil-5T-SU	
Primary Voltage	380	
Primary Max Current	<u>526.32A</u>	
Primary Markings	<u>X1-X2</u>	
Primary Terminals	<u>Pads</u>	
Secondary Voltage	415	
Secondary Max Current	481.93A	
Secondary Markings	H1-H2	
Secondary Terminals	<u>Pads</u>	
Primary Taps	+/- 2 x 2.5%	
Conductor Material	Copper	
BIL (Insulation) Level	<u>10kV</u>	
Efficiency (@35% Load) %	98.74% (DOE 2016/NRCan 2019)	
Impedance Range	4.0 - 6.0%	
Sound (db)	<u>55</u>	
Enclosure Type	NEMA 3R Indoor	
Enclosure Size	<u>E3R-9S</u>	
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey	
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered	
Temperatue Rise	150°C	



#### **OFFICIAL QUOTE**



## 200KVA 380 VOLTS TO 415 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

-	Insuation Class	150°C
	Country/Manufacturer	Canada/RPM
	Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey