

OFFICIAL QUOTE

200KVA 380 VOLTS TO 575 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





200KVA 380 VOLTS TO 575 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$14,843.12 USD

Single Phase Isolation Transformer with a capacity of 200kVA, transforming 380 Volts to 575 Volts

SKU: SC200F-J1/Z3 Categories: Isolation Transformers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Isolation Transformer with a capacity of 200kVA, transforming 380 Volts to 575 Volts



OFFICIAL QUOTE

200KVA 380 VOLTS TO 575 VOLTS SINGLE PHASE ISOLATION TRANSFORMER



PRODUCT SPECIFICATIONS

Weight	1170 lbs
Phases	1
kVA	200
Connection	1Ph-2coil-5T-SU
Primary Voltage	380
Primary Max Current	<u>526.32A</u>
Primary Markings	<u>X1-X2</u>
Primary Terminals	Pads
Secondary Voltage	<u>575</u>
Secondary Max Current	<u>347.83A</u>
Secondary Markings	<u>H1-H2</u>
Secondary Terminals	Pads
Primary Taps	<u>+/-2 x 2.5%</u>
Conductor Material	Copper
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	98.74% (DOE 2016/NRCan 2019)
Impedance Range	<u>4.0 - 6.0%</u>
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-9S</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	<u>150°C</u>

The quote is valid 30 days from 12 June 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.



OFFICIAL QUOTE

200KVA 380 VOLTS TO 575 VOLTS SINGLE PHASE ISOLATION TRANSFORMER



Insuation Class	<u>150°C</u>
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey