


OFFICIAL QUOTE

200VA 110 VOLTS TO 115/230 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





200VA 110 VOLTS TO 115/230 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$13,790.70 CAD


Single Phase Isolation Transformer with a capacity of 200kVA, transforming 110 Volts to 115/230 Volts

SKU: SA200A2-K1/Z3

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Isolation Transformer with a capacity of 200kVA, transforming 110 Volts to 115/230 Volts



OFFICIAL QUOTE



200VA 110 VOLTS TO 115/230 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS		
Weight	1015 lbs	
Phases	1	
kVA	200	
Connection	1Ph-2coil-5T-SU	
Primary Voltage	110	
Primary Max Current	<u>1818.18A</u>	
Primary Markings	<u>X1-X2</u>	
Primary Terminals	<u>Pads</u>	
Secondary Voltage	115/230	
Secondary Max Current	<u>1739.13A</u>	
Secondary Markings	<u>H1-H2</u>	
Secondary Terminals	<u>Pads</u>	
Primary Taps	+/- 2 x 2.5%	
Conductor Material	Aluminum	
BIL (Insulation) Level	<u>10kV</u>	
Efficiency (@35% Load) %	98.74% (DOE 2016/NRCan 2019)	
Impedance Range	4.0 - 6.0%	
Sound (db)	<u>55</u>	
Enclosure Type	NEMA 3R Indoor	
Enclosure Size	<u>E3R-9S</u>	
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey	
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered	
Temperatue Rise	150°C	



OFFICIAL QUOTE



200VA 110 VOLTS TO 115/230 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey