

#### **OFFICIAL QUOTE**

## 200VA 230 VOLTS TO 110/220 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





# 200VA 230 VOLTS TO 110/220 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$13,239.07 CAD


Single Phase Isolation Transformer with a capacity of 200kVA, transforming 230 Volts to 110/220 Volts

SKU: SA200C1-K2/Z3

**Categories:** <u>Isolation Transformers</u>

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Isolation Transformer with a capacity of 200kVA, transforming 230 Volts to 110/220 Volts



### **OFFICIAL QUOTE**



## 200VA 230 VOLTS TO 110/220 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

#### PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS     |  |  |
|----------------------------|--|--|
| Weight                     | 1015 lbs   |  |
| Phases                     | 1  |  |
| kVA                        | 200  |  |
| Connection                 | 1Ph-2coil-5t-SD  |  |
| Primary Voltage            | 230  |  |
| Primary Max Current        | 869.57A  |  |
| Primary Markings           | H1-H2  |  |
| Primary Terminals          | <u>Pads</u>  |  |
| Secondary Voltage          | 110/220  |  |
| Secondary Max Current      | 1818.18A   |  |
| Secondary Markings         | <u>X1-X2</u>   |  |
| Secondary Terminals        | <u>Pads</u>  |  |
| Primary Taps               | +/- 2 x 2.5%   |  |
| Conductor Material         | Aluminum   |  |
| BIL (Insulation) Level     | 10kV   |  |
| Efficiency (@35% Load) %   | 98.74% (DOE 2016/NRCan 2019)   |  |
| Impedance Range            | 4.0 - 6.0%   |  |
| Sound (db)                 | <u>55</u>  |  |
| Enclosure Type             | NEMA 3R Indoor   |  |
| Enclosure Size             | <u>E3R-9S</u>  |  |
| Finish/Colour              | Polyester Powder Coat - ANSI/ASA 61 Grey   |  |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |  |
| Temperatue Rise            | 150°C  |  |



### **OFFICIAL QUOTE**



## 200VA 230 VOLTS TO 110/220 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

| Insuation Class      | 150°C                                    |
|----------------------|--|
| Country/Manufacturer | Canada/RPM                               |
| Finish/Colour        | Polyester Powder Coat - ANSI/ASA 61 Grey |