



225KVA 115 VOLTS TO 600Y/347 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$20,920.90 CAD

Three Phase Isolation Transformer with a capacity of 225kVA, transforming 115 Volts to 600Y/347 Volts

SKU: BA225A1-Q/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 225kVA, transforming 115 Volts to 600Y/347 Volts



PRODUCT SPECIFICATIONS

Weight	1750 lbs
Phases	3
kVA	225
Connection	3Ph-DY-5CT-SU
Primary Voltage	115
Primary Max Current	1129.6A
Primary Markings	X1-X2-X3
Primary Terminals	Pads
Secondary Voltage	600Y/347
Secondary Max Current	216.51A
Secondary Markings	H0-H1-H2-H3
Secondary Terminals	Pads
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	98.94% (DOE 2016/NRCan 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	55
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-9
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



OFFICIAL QUOTE

225KVA 115 VOLTS TO 600Y/347
VOLTS THREE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey