

OFFICIAL QUOTE

225VA 110 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER





225VA 110 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER


\$23,773.75 CAD

Three Phase Isolation Transformer with a capacity of 225kVA, transforming 110 Volts to 220Y/127 Volts

SKU: BA225A2-S2/Z3

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



$$X_2$$
 X_2
 X_3
 X_4
 X_4

Three Phase Isolation Transformer with a capacity of 225kVA, transforming 110 Volts to 220Y/127 Volts



OFFICIAL QUOTE



225VA 110 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

| Weight | 1750 lbs |
|----------------------------|--|
| Phases | 3 |
| kVA | 225 |
| Connection | 3Ph-DY-5CT-SU |
| Primary Voltage | 110 |
| Primary Max Current | 1180.94A |
| Primary Markings | <u>X1-X2-X3</u> |
| Primary Terminals | <u>Pads</u> |
| Secondary Voltage | <u>220Y/127</u> |
| Secondary Max Current | 590.47A |
| Secondary Markings | <u>H0-H1-H2-H3</u> |
| Secondary Terminals | <u>Pads</u> |
| Primary Taps | +/- 2 x 2.5% |
| Conductor Material | Aluminum |
| BIL (Insulation) Level | 10kV |
| Efficiency (@35% Load) % | 98.94% (DOE 2016/NRCan 2019) |
| Impedance Range | 4.0 - 6.0% |
| Sound (db) | <u>55</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | E3R-9 |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Temperatue Rise | 150°C |



OFFICIAL QUOTE



225VA 110 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER

| Insuation Class | <u>150°C</u> | - |
|----------------------|--|---|
| Country/Manufacturer | Canada/RPM | |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey | |