



225VA 550 VOLTS TO 575Y/332 VOLTS THREE PHASE ISOLATION TRANSFORMER


\$25,225.20 CAD

Three Phase Isolation Transformer with a capacity of 225kVA, transforming 550 Volts to 575Y/332 Volts

SKU: BC225J2-Q1/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 225kVA, transforming 550 Volts to 575Y/332 Volts



PRODUCT SPECIFICATIONS

Weight	1680 lbs
Phases	3
kVA	225
Connection	3Ph-DY-5CT-SU
Primary Voltage	550
Primary Max Current	236.19A
Primary Markings	X1-X2-X3
Primary Terminals	600 MCM – 2
Secondary Voltage	575Y/332
Secondary Max Current	225.92A
Secondary Markings	H0-H1-H2-H3
Secondary Terminals	600 MCM – 2
Primary Taps	+/- 2 x 2.5%
Conductor Material	Copper
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	98.94% (DOE 2016/NRCAN 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	55
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-9
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperature Rise	150°C



OFFICIAL QUOTE

225VA 550 VOLTS TO 575Y/332
VOLTS THREE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey