



250KVA 550 VOLTS TO 230/460 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$15,501.02 CAD

Single Phase Isolation Transformer with a capacity
of 250kVA, transforming 550 Volts to 230/460
Volts

SKU: SA250J2-L1/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Isolation Transformer with a capacity of 250kVA, transforming 550 Volts to 230/460 Volts



PRODUCT SPECIFICATIONS

Weight	1225 lbs
Phases	1
kVA	250
Connection	1Ph-2coil-5t-SD
Primary Voltage	550
Primary Max Current	454.55A
Primary Markings	H1-H2
Primary Terminals	Pads
Secondary Voltage	230/460
Secondary Max Current	1086.96A
Secondary Markings	X1-X2
Secondary Terminals	Pads
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	98.80% (DOE 2016/NRCan 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	55
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-9S
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



OFFICIAL QUOTE

250KVA 550 VOLTS TO 230/460
VOLTS SINGLE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey