



250VA 550 VOLTS TO 460 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$21,369.53 CAD

Single Phase Isolation Transformer with a capacity of 250kVA, transforming 550 Volts to 460 Volts

SKU: SC250J2-H1/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Isolation Transformer with a capacity of 250kVA, transforming 550 Volts to 460 Volts



PRODUCT SPECIFICATIONS

| | |
|----------------------------|--|
| Weight | 1308 lbs |
| Phases | 1 |
| kVA | 250 |
| Connection | 1Ph-2coil-5t-SD |
| Primary Voltage | 550 |
| Primary Max Current | 454.55A |
| Primary Markings | H1-H2 |
| Primary Terminals | Pads |
| Secondary Voltage | 460 |
| Secondary Max Current | 543.48A |
| Secondary Markings | X1-X2 |
| Secondary Terminals | Pads |
| Primary Taps | +/- 2 x 2.5% |
| Conductor Material | Copper |
| BIL (Insulation) Level | 10kV |
| Efficiency (@35% Load) % | 98.80% (DOE 2016/NRCan 2019) |
| Impedance Range | 4.0 – 6.0% |
| Sound (db) | 55 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | E3R-9S |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Temperatue Rise | 150°C |



OFFICIAL QUOTE

250VA 550 VOLTS TO 460 VOLTS
SINGLE PHASE ISOLATION
TRANSFORMER



| | |
|----------------------|--|
| Insuation Class | 150°C |
| Country/Manufacturer | Canada/RPM |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |