


OFFICIAL QUOTE

25KVA 115 VOLTS TO 110 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





25KVA 115 VOLTS TO 110 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$3,810.24 CAD

Single Phase Isolation Transformer with a capacity of 25kVA, transforming 115 Volts to 110 Volts

SKU: SC25A1-A2/Z3

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Isolation Transformer with a capacity of 25kVA, transforming 115 Volts to 110 Volts



OFFICIAL QUOTE



25KVA 115 VOLTS TO 110 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

| Weight | 225 lbs |
|----------------------------|--|
| Phases | 1 |
| kVA | <u>25</u> |
| Connection | 1Ph-2coil-5t-SD |
| Primary Voltage | 115 |
| Primary Max Current | 217.39A |
| Primary Markings | H1-H2 |
| Primary Terminals | 600 MCM - 2 |
| Secondary Voltage | 110 |
| Secondary Max Current | 227.27A |
| Secondary Markings | <u>X1-X2</u> |
| Secondary Terminals | 600 MCM - 2 |
| Primary Taps | +/- 2 x 2.5% |
| Conductor Material | Copper |
| BIL (Insulation) Level | 10kV |
| Efficiency (@35% Load) % | 98.00% (DOE 2016/NRCan 2019) |
| Impedance Range | 4.0 - 6.0% |
| Sound (db) | 45 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-6</u> |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Temperatue Rise | 150°C |



OFFICIAL QUOTE



25KVA 115 VOLTS TO 110 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

| Insuation Class | 150°C |
|----------------------|--|
| Country/Manufacturer | Canada/RPM |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |