

OFFICIAL QUOTE

2KVA 208 VOLTS TO 230/460 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





2KVA 208 VOLTS TO 230/460 VOLTS SINGLE PHASE ISOLATION TRANSFORMER


\$1,029.57 CAD

Single Phase Isolation Transformer with a capacity of 2kVA, transforming 208 Volts to 230/460 Volts

SKU: SC2B-L1

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Isolation Transformer with a capacity of 2kVA, transforming 208 Volts to 230/460 Volts



OFFICIAL QUOTE



2KVA 208 VOLTS TO 230/460 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

Watala	FO III a
Weight	50 lbs
Phases	1
kVA	2
Connection	1Ph-1coil-3T-SU
Primary Voltage	208
Primary Max Current	9.62A
Primary Markings	<u>X1-X2</u>
Primary Terminals	#2-14 AWG
Secondary Voltage	230/460
Secondary Max Current	8.7A
Secondary Markings	H1-H2
Secondary Terminals	#2-14 AWG
Primary Taps	+/- 1 x 5%
Conductor Material	Copper
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	<u>5.0 – 7.0%</u>
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	<u>E1-1</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	<u>115°C</u>



OFFICIAL QUOTE



2KVA 208 VOLTS TO 230/460 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

Insuation Class	115°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey