

**OFFICIAL QUOTE** 

2KVA 460 VOLTS TO 220/440 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





### 2KVA 460 VOLTS TO 220/440 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

## \$1,029.57 CAD

Single Phase Isolation Transformer with a capacity of 2kVA, transforming 460 Volts to 220/440 Volts

SKU: SC2H1-L2 Categories: Isolation Transformers

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Isolation Transformer with a capacity of 2kVA, transforming 460 Volts to 220/440 Volts



**OFFICIAL QUOTE** 

# 

### 2KVA 460 VOLTS TO 220/440 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

#### **PRODUCT SPECIFICATIONS**

| Weight                     | 50 lbs                                                                                  |
|----------------------------|-----------------------------------------------------------------------------------------|
| Phases                     | 1                                                                                       |
| kVA                        | 2                                                                                       |
| Connection                 | 1Ph-1coil-3T-SD                                                                         |
| Primary Voltage            | <u>460</u>                                                                              |
| Primary Max Current        | <u>4.35A</u>                                                                            |
| Primary Markings           | <u>H1-H2</u>                                                                            |
| Primary Terminals          | <u>#2-14 AWG</u>                                                                        |
| Secondary Voltage          | 220/440                                                                                 |
| Secondary Max Current      | <u>9.09A</u>                                                                            |
| Secondary Markings         | <u>X1-X2</u>                                                                            |
| Secondary Terminals        | <u>#2-14 AWG</u>                                                                        |
| Primary Taps               | <u>+/- 1 x 5%</u>                                                                       |
| Conductor Material         | <u>Copper</u>                                                                           |
| BIL (Insulation) Level     | <u>10kV</u>                                                                             |
| Efficiency (@35% Load) %   | <u>N/A</u>                                                                              |
| Impedance Range            | <u>5.0 – 7.0%</u>                                                                       |
| Sound (db)                 | <u>40</u>                                                                               |
| Enclosure Type             | NEMA 1                                                                                  |
| Enclosure Size             | <u>E1-1</u>                                                                             |
| Finish/Colour              | Polyester Powder Coat – ANSI/ASA 61 Grey                                                |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015<br>Registered |
| Temperatue Rise            | <u>115°C</u>                                                                            |

The quote is valid 30 days from 13 June 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.



**OFFICIAL QUOTE** 

### 2KVA 460 VOLTS TO 220/440 VOLTS SINGLE PHASE ISOLATION TRANSFORMER



| Insuation Class      | <u>115°C</u>                             |
|----------------------|------------------------------------------|
| Country/Manufacturer | Canada/RPM                               |
| Finish/Colour        | Polyester Powder Coat – ANSI/ASA 61 Grey |