



300KVA 208 VOLTS TO 550Y/318 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$28,672.00 CAD

Three Phase Isolation Transformer with a capacity of 300kVA, transforming 208 Volts to 550Y/318 Volts

SKU: BA300B-Q2/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 300kVA, transforming 208 Volts to 550Y/318 Volts



PRODUCT SPECIFICATIONS

| | |
|----------------------------|--|
| Weight | 2100 lbs |
| Phases | 3 |
| kVA | 300 |
| Connection | 3Ph-DY-5CT-SU |
| Primary Voltage | 208 |
| Primary Max Current | 832.72A |
| Primary Markings | X1-X2-X3 |
| Primary Terminals | Pads |
| Secondary Voltage | 550Y/318 |
| Secondary Max Current | 314.92A |
| Secondary Markings | H0-H1-H2-H3 |
| Secondary Terminals | Pads |
| Primary Taps | +/- 2 x 2.5% |
| Conductor Material | Aluminum |
| BIL (Insulation) Level | 10kV |
| Efficiency (@35% Load) % | 99.02% (DOE 2016/NRCAN 2019) |
| Impedance Range | 4.0 – 6.0% |
| Sound (db) | 55 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | E3R-9 |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Temperature Rise | 150°C |



OFFICIAL QUOTE

300KVA 208 VOLTS TO 550Y/318
VOLTS THREE PHASE ISOLATION
TRANSFORMER



| | |
|----------------------|--|
| Insuation Class | 150°C |
| Country/Manufacturer | Canada/RPM |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |