

OFFICIAL QUOTE

300KVA 230 VOLTS TO 230Y/133 VOLTS THREE PHASE ISOLATION TRANSFORMER





300KVA 230 VOLTS TO 230Y/133 VOLTS THREE PHASE ISOLATION TRANSFORMER


\$35,721.00 CAD

Three Phase Isolation Transformer with a capacity of 300kVA, transforming 230 Volts to 230Y/133 Volts

SKU: BC300C1-S1/Z3

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 300kVA, transforming 230 Volts to 230Y/133 Volts



OFFICIAL QUOTE



300KVA 230 VOLTS TO 230Y/133 VOLTS THREE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

| Weight | 2055 lbs |
|----------------------------|--|
| Phases | <u>3</u> |
| kVA | 300 |
| Connection | 3Ph-DY-5CT-SU |
| Primary Voltage | 230 |
| Primary Max Current | 753.07A |
| Primary Markings | H1-H2-H3 |
| Primary Terminals | <u>Pads</u> |
| Secondary Voltage | 230Y/133 |
| Secondary Max Current | 753.07A |
| Secondary Markings | <u>X0-X1-X2-X3</u> |
| Secondary Terminals | Pads |
| Primary Taps | +/- 2 x 2.5% |
| Conductor Material | Copper |
| BIL (Insulation) Level | 10kV |
| Efficiency (@35% Load) % | 99.02% (DOE 2016/NRCan 2019) |
| Impedance Range | 4.0 - 6.0% |
| Sound (db) | <u>55</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | E3R-9 |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Temperatue Rise | 150°C |



OFFICIAL QUOTE



300KVA 230 VOLTS TO 230Y/133 VOLTS THREE PHASE ISOLATION TRANSFORMER

| Insuation Class | 150°C |
|----------------------|--|
| Country/Manufacturer | Canada/RPM |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |