




OFFICIAL QUOTE

30KVA 200 VOLTS TO 600Y/347
VOLTS THREE PHASE ISOLATION
TRANSFORMER



30KVA 200 VOLTS TO 600Y/347 VOLTS THREE PHASE ISOLATION TRANSFORMER



\$5,841.47 CAD

Three Phase Isolation Transformer with a capacity of 30kVA, transforming 200 Volts to 600Y/347 Volts

SKU: BC30B1-Q/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 30kVA, transforming 200 Volts to 600Y/347 Volts



OFFICIAL QUOTE

30KVA 200 VOLTS TO 600Y/347 VOLTS THREE PHASE ISOLATION TRANSFORMER



PRODUCT SPECIFICATIONS

Weight	308 lbs
Phases	3
kVA	30
Connection	3Ph-DY-5T-SU
Primary Voltage	200
Primary Max Current	86.6A
Primary Markings	X1-X2-X3
Primary Terminals	#2/0-6 AWG
Secondary Voltage	600Y/347
Secondary Max Current	28.87A
Secondary Markings	H0-H1-H2-H3
Secondary Terminals	#2/0-6 AWG
Primary Taps	+/- 2 x 2.5%
Conductor Material	Copper
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	98.23% (DOE 2016/NRCan 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-6
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



OFFICIAL QUOTE

**30KVA 200 VOLTS TO 600Y/347
VOLTS THREE PHASE ISOLATION
TRANSFORMER**



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey